

Honey 2

by **Carter**
Enterprises

Accuracy Defined Through Design



General Directions for Use:

Safety Selection Screw:

The Honey 2 gives you your choice of how to operate the safety mechanism. For the safety to function automatically simply screw the safety selection screw in to increase spring tension on the safety. In this mode you will need to physically hold the safety in while drawing and letting down. When ready to execute the shot, simply let your thumb up on the safety and the spring will push the safety out on it's own. **The Honey 2 is shipped in this mode.**

For the safety to function manually, simply back out the screw until the safety will stay locked in the closed position by itself. In this mode, you will need to push the safety in and lock it while drawing and letting down. In order to disengage the safety and execute the shot, you will need to manually disengage the safety by pushing the safety out with your thumb.

Recommend Use:

When loading the Honey 2, it is best to start with the release rotates so that the back of the hinge is resting against the stop on the case. With the safety engaged and the head floating, this will allow the magnet to pull the hook and half moon together for the safest amount of sear engagement. Once tension is applied to the hook by pulling on your d-loop, you can now draw back safely with your entire hand. With the safety engaged you can anchor and get on target. Disengage the safety and execute the shot in a slow controlled motion. Always re-engage the safety before letting down in both manual and automatic mode. **Carter Enterprises always recommends becoming accustomed to the function of the release before attempting to use it on archery tackle.**